

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 2074'	T. Miss _____ Missing	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____ 7768'	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 3098'	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____ 4430'	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____ 7938'	T. Morrison _____	T. _____
T. Tubb _____ 5757'	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____ 6508'	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____ 7134'	T. Fusselman _____ 7822'	T. Chinle _____	T. _____
T. Penn. _____ 7562'	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____ 7682'	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
3098'	4430'	1332'	San Andres				
4430'	5757'	1327'	Glorieta				
5757'	6508'	751'	Tubb				
6508'	7134'	626'	Abo Shale				
7134'	7562'	428'	Wolfcamp				
7562'	7682'	120'	Penn Lime				
7682'	7768'	86'	Cisco				
7768'	7822'	54'	Silurian				
7822'	7938'	116'	Fusselman				
7938'	TD	22'	Granite Wash				