

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

<p align="center"><b>SUNDRY NOTICES AND REPORTS ON WELLS</b></p> <p align="center"><small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small></p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p> <p>5. State Oil &amp; Gas Lease No. --</p>
<p>OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/></p> <p>6. Name of Operator <b>Coquina Oil Corporation</b></p> <p>7. Address of Operator <b>P. O. Drawer 2960 Midland, TX 79702</b></p> <p>8. Location of Well UNIT LETTER <b>C</b> <b>660</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM THE <b>West</b> LINE, SECTION <b>10</b> TOWNSHIP <b>6S</b> RANGE <b>32E</b> NMPM.</p>		<p>7. Unit Agreement Name --</p> <p>8. Farm or Lease Name <b>Clemmons</b></p> <p>9. Well No. <b>1</b></p> <p>10. Field and Pool, or Wildcat <b>Wildcat</b></p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) <b>4467.6' GR</b></p>		<p>12. County <b>Roosevelt</b></p>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:      SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐  
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 8038'. Ran 6 jts, 187' of 5 1/2", 15.5, K-55, STC; 133 jts, 5745', of 5 1/2", 15#, K-55, LTC; and 50 jts, 2108' of 5 1/2", 17#, K-55, LTC. Set 5 1/2" casing at 8038'. Cemented w/1600 sx pacesetter lite w/3# salt, 1/4# cello-seal/sx. Tailed w/325 sx C1 C Displaced w/175.5 bbls fresh wtr. Final pump pressure 3100 psi. Set slips. Cut off csg. Rel rig 10:00 PM 8/11/80. Ran temp survey. TOC 6100'. Tagged cmt inside csg at 7348'. MORT.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED G. L. Crain TITLE Drilling Manager DATE 8-12-80

APPROVED BY Larry Sexton TITLE Drilling Manager DATE AUG 15 1980

CONDITIONS OF APPROVAL, IF ANY: