

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		7. Unit Agreement Name
2. Name of Operator Enserch Exploration, Inc.		8. Farm or Lease Name Rader
3. Address of Operator P. O. Box 4815, Midland, Texas 79704		9. Well No. 2
4. Location of Well UNIT LETTER <u>E</u> <u>1880</u> FEET FROM THE <u>North</u> LINE AND <u>560</u> FEET FROM THE <u>West</u> LINE, SECTION <u>32</u> TOWNSHIP <u>5S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat S. Peterson (Fusselman)
15. Elevation (Show whether DF, RT, GR, etc.) 4384.5' GR		12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work performed from March 18 to March 31, 1983:

Set CIBP at 7827'.
Laid 35 sacks Class H cement from 7827' to 7792'.
Cut off 5-1/2" casing at 3700'.
Laid 25 sacks Class H cement from 5146' to 5121'.
Laid 100 sacks Class H cement from 3719' to 3500'.
Laid 355 sacks Class H cement from 2046' to 1835'.
Laid 13 sacks Class H cement from 30' to surface.
Cut off 9-5/8" casing head. Welded 9-5/8" x 1/2" steel plate. Installed dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNER <u>H. E. Cornelsen</u>	TITLE <u>Production Supervisor</u>	DATE <u>4/5/83</u>
APPROVED BY <u>Ronald M. [Signature]</u> TITLE <u>OIL & GAS INSPECTOR</u> DATE <u>JUN 28 1983</u>		
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

APR 8 1983

O.C.D.
HOBUS OFFICE