

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-		7. Unit Agreement Name
Name of Operator SUN OIL COMPANY (DELAWARE)		8. Farm or Lease Name EDNA NELSON
Address of Operator P. O. BOX 30; DALLAS, TEXAS 75221		9. Well No. 1
Location of Well UNIT LETTER J 1980 FEET FROM THE SOUTH LINE AND 1980 FEET FROM THE EAST LINE, SECTION 13 TOWNSHIP 3S RANGE 31E NMPM.		10. Field and Pool, or Wildcat WILDCAT
15. Elevation (Show whether DF, RT, GR, etc.) 4248.2 GR		12. County ROOSEVELT

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> FULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> OTHER <input type="checkbox"/>
---	--	---	---

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

DRILLED 12-1/4" HOLE 395-2693'. SET 8-5/8" O.D. 24# K-55 STC NEW CONDITION INTERMEDIATE CASING AT 2693'. CEMENTED WITH 1025 SX HALLIBURTON LIGHT + 15#/SK SALT + 3#/SK GILSONITE + 1/4# /SK FLOCELE. TAILED IN WITH 200 SX CLASS C + 2% CACL. CEMENT CIRCULATED TO SURFACE. JOB COMPLETE AT 4:39 A.M. ON 11-10-80. WOC 24 HOURS. TESTED BOPs TO 3000 PSI FOR 30 MINUTES - NO LEAK-OFF.

API NO.: 30-041-20553

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>R. T. Harris</u> R. T. HARRIS Drilling Engineer Drilling Engineer	TITLE SR. DRILLING ENGINEER	DATE NOVEMBER 18, 1980
REVIEWED BY <u>Drilling Engineer</u> REVIEWED BY <u>Drilling Engineer</u>	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		