

CONSERVATION DIVISION

P. O. BOX 2000

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG WELLS IN A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR TO DEEPEN OR PLUG WELLS FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

7. Name of Operator
Enserch Exploration, Inc.

8. Address of Operator
1230 River Bend Drive - Suite 136 - Dallas, Texas 75247

9. Location of Well
UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM
THE East LINE, SECTION 6 TOWNSHIP 5S RANGE 33E N.M.P.M.

5a. Indicate Type of Lease State ☐ Fee ☒
6. State Oil & Gas Lease No. 30-041-20556
7. Unit Agreement Date
8. Name of Lease Land Finley
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Roosevelt

15. Elevation (Show whether DF, RT, GR, etc.)
4501.4

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

Drilling Operations

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole on 12-20-80. Drilled 17-1/2" hole to 360'. Ran and cemented 13-3/8", 48#, casing at 341' with 425 sacks Class "C" + 2% CaCl₂. Top of cement at 55'. Topped out annulus with 100 sacks Class "C" + 2% CaCl₂. Drilled 12-1/4" hole to 2019'. Ran and cemented 9-5/8", 36#, casing at 1996' with 740 sacks light and 250 sacks Class "C" with 2% CaCl₂. Circulated cement to surface. Nippled up and tested BOP's and casing to 1500 psi. Drilled 8-3/4" hole to 8500' total depth. Ran DLL from 8511' to 1998' (loggers depth), FDC-CNL from 8506' to 1998' and Sonic log from 8506' to 1998'. Ran 5-1/2", 17# and 15.5# casing at 8510'. (15.5# set to 7645' and 17# from 7645' to 8510'). Cemented with 525 sacks (557 cu/ft.) Class "H" + 0.6% Halad 22-A + 6# salt/sack + 75% CFR-2 mixed at 16.4 ppg. Bumped plug with 2000 psi on January 18, 1981. Waited on cement. Released Rig on 1-18-81. Waiting on completion unit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

C. H. Peoples
C. H. Peoples

TITLE Regional Drilling Manager

DATE February 26, 1981

Orig. Signed by

Jerry Sexton

Dist. to Super

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: