

N. M. OIL CONS. COMMISSION
P. O. BOX 1
HOBBS, NEW MEXICO 88240
UNITED STATES

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir; use Form 9-331-C for such proposals.)

1. NAME OF WELL

2. NAME OF OPERATOR

Sundance Oil Company

3. ADDRESS OF OPERATOR

1675 Larimer Street, Suite 800, Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below)

AT SURFACE: 1980' FNL 610' FWL Unit E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE

CHANGE ZONES

ABANDON*

(other) Completion

SUBSEQUENT REPORT OF:

RECEIVED

RECEIVED

OCT 19 1982

U.S. GEOLOGICAL SURVEY

HOBBS, NEW MEXICO

RECEIVED

OIL & GAS

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2/20/81 Perforated 4158'-60', 4162'-68', 4170'-4176', 4188'-4192', 4202'-4208' with 2 SPF. 2/21/81 Acidize with 5000 gal. 20% NE acid. 2/24/81 Swabbed well dry. 3/3/81 Set packer at 4147'. 3/7/81 Swabbed 40 Bbls water, no trace of oil. 3/9/81 Set CIBP at 4140'. Cmt'd BP with 1 sx cement (16'). Perforated P-2 zone from 4088'-92' and 4101-05' with 2 SPF. 3/11/81 Set packer at 4027'. Pumped 4000 gal. acid dropping 5 ball sealers every 500 gal. Swabbed back 45 BTF. 3/12/81 Swabbed 35 BTF - 55 oil. 3/13/81 Acidized with 5000 gal. 28% NE acid. 3/14/81 Swabbed 80 BTF with a trace of oil. 4/24/81 Perforated 1800-1810'. Set RBP at 1856'. 4/28/81 Swabbed 47 Bbls of water (muddy) S.I. 4/29/81 Well temporarily abandoned.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Drilling Manager DATE May 24, 1982

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY
CONDITIONS OF

OCT 15 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

OCT 26 1982

O.C.D.
HOBBS OFFICE