

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry		7. Unit Agreement Name
2. Name of Operator Enserch Exploration, Inc.		8. Farm or Lease Name Lambirth
3. Address of Operator P. O. Box 4815, Midland, Texas 79704		9. Well No. 11
4. Location of Well UNIT LETTER M, 660 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 1 TOWNSHIP 6S RANGE 33E NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4424.9' GR		12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work performed from 3/31/83 to 4/9/83:

Set CIBP at 3885'

Laid 5 sacks Class H cement from 3870' to 3835'.

Cut off 5-1/2" casing at 3410'.

Laid 40 sacks Class H cement from 3440' to 3340'.

Laid 100 sacks Class H cement from 2046' to 1922'.

Laid 40 sacks Class H cement from 1612' to 1512'.

Laid 15 sacks Class H cement from 30' to surface.

Cut off 9-5/8" casing and welded on 9-5/8" x 1/2" steel plate.

Installed dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>H. F. Burnett</u>	TITLE <u>Prod. Superintendent</u>	DATE <u>5/26/83</u>
APPROVED BY <u>David Starnock</u>		
TITLE <u>OIL & GAS INSPECTOR</u>		
DATE <u>MAY 1 1983</u>		

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
MAY 31 1963
O. C. C.
HOBBS