Form 9-331 Dec. 1973

Form Approved.

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

(other) RAN PRODUCTION CASING

REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** ABANDON*

ويهاف وزراتهما

Dec. 1973	Budget Bureau No. 42-R1424		
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE NM-15019		
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas	Cone Federal		
well well other	9. WELL NO.		
2. NAME OF OPERATOR	<u>31-Y</u>		
SUNDANCE OIL COMPANY MAD 1 1 1004	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Tomahawk, San Andres		
#910, 1776 Lincoln St., Denver, CO : 80203	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17.	AREA		
#910, 1776 Lincoln St., Denver, CO : 80203 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17.) below.)	INE NW Section 19, T.7S., R.32E.		
AI SURFACE: /ZU' FNL, 1/81 FWL, UNIC C	12. COUNTI ON PARISH 13. STATE		
AT TOP PROD. INTERVAL:	Roosevelt New Mexico		
AT TOTAL DEPTH: Same	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 4408' GL, 4420' KB		
DECLIEST FOR APPROVAL TO: SUBSECUENT REPORT OF	t		

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

SUBSEQUENT REPORT OF:

Drilled 7 7/8" hole from 1801' to 4250' (TD). Schlumberger ran SNP-GR & DLL-RXO-GR. Ran 119 jts. 4 1/2", 10.5# casing. Set at 4249'. Cemented w/300 sx class C 50/50 Pozmix, 8# salt, 1/4# flocele, 2% gel. PD at 10:25 p.m. on 2/27/81. Pressured up to 800#, okay. Rig released at 11 p.m. 2/27/81. WOCU.

Subsurface Safety Valve: Manu. and Type		Set @	Ft.
18. I hereby certify that the foregoing is true and correct			
SIGNED Wice President,	DATE .	March 11, 1981	
Richard O. Dimit Production ACCEPTED FOR RECORD space for Federal or State office us.	e)		_
PETER W. CHESTER	DATE		
conditions of Approval, MAR 1 9 1981			
U.S. GEOLOGICAL SURVEY			