Form 9-331 Dec. 1973

Form Approved.

UNITED STATES DEPARTMENT OF THE INTERIOR

| | Budget Bureau No. 42-R14 | | | | |
|--------|---|--|--|--|--|
| | 5. LEASE | | | | |
| | NM-15019 | | | | |
| | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME | | | | |
| | 7. UNIT AGREEMENT NAME | | | | |
| îŧ | | | | | |
| | 8. FARM OR LEASE NAME | | | | |
| | Cone Federal | | | | |
| | 9. WELL NO. | | | | |
| E. | 31-Y | | | | |
|) | 10. FIELD OR WILDCAT NAME | | | | |
| | Tomahawk, San Andres | | | | |
| 7 | 11. SEC., T., R., M., OR BLK. AND SURVEY OF | | | | |
| , | NE NW Section 19, T.7S., R.32E. | | | | |
| | 12. COUNTY OR PARISH 13. STATE | | | | |
| | Roosevelt New Mexico | | | | |
| -, | 14. API NO. | | | | |
| | | | | | |

GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) gas weil 💢 other well J.S. GEBEULDONO, L SU 2. NAME OF OPERATOR HOBBE, NEW MEXICO SUNDANCE OIL COMPANY 3. ADDRESS OF OPERATOR #910, 1776 Lincoln St., Denver, CO 80203 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1 AT SURFACE: 720' FNL, 1781' FWL, Unit C AT TOP PROD. INTERVAL: AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 4408' GL, 4420' KB SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone change on Form 9-330.) PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* SET SURFACE CASING 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Received verbal approval from BLM and USGS to move well location. Spudded $12\frac{1}{4}$ " surface hole at 5:45 p.m. 2/19/81. Drilled to 1801' and ran 43 jts. of 24# 8 5/8" surface casing. Set at 1773'. Cemented w/300 sx Class C Econolite followed w/200 sx Class C, 2% CaCl₂. Circulated 18 sx. up to 1000#, held okay. PD at 7 a.m. on 2/22/81. WOC.

| | | | • | | |
|---|--|--|-------------|--|-----|
| Subsurface Safety Valve: Manu. and Ty | /pe | | Set @ | | Ft. |
| <i>1</i> | | | | | |
| 18. I hereby certify that the foregoing is true and correct | | | | | |
| SIGNED LOUIS AND | Mul JITLE V-P, Production | DATE _ | February 27 | , 1981 | |
| Richard U. Dimit | (This space for Federal or State office use) | ······································ | | | _ |
| APPROVED BY | VED BY TITLE | DATE | | - <u>- </u> | |
| CONDITIONS OF APPROVAL, IF ANY: | | | | + <u>1</u> 1. | |