	· · · ·	
NO. OF COPIES RECEIVED		Form C-103
DISTRIBUTION		Supersedes Old C-102 and C-103
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE		
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE		State Fee X
OPERATOR		5. State Oil & Gas Lease No.
(DO NOT USE THIS FORM FOR P USE "APPLIC	RY NOTICES AND REPORTS ON WELLS ROPOSALS TO DRILL OR TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. NTION FOR PERMIT	
1. OIL GAS WELL	отнея-	7, Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name	
Enserch Exploration, 1	Wilson	
3. Address of Operator	9. Well No.	
P. O. Box 4815, Midlar	1	
4. Location of Well	10, Field and Pool, or Wildcat	
UNIT LETTERF	Wildcat	
	tion 6 5S RANGE 33E NMPM.	
	12. County	
	4502.1' GR	Roosevelt
^{16.} Check	Appropriate Box To Indicate Nature of Notice, Report or Ot	her Data
		T REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS.	ALTERING CASING PLUG AND ABANDONMENT mpletion Attempt
OTHER		
	Or any the protocol protocol portinent details and give pertinent dates including	estimated date of starting any proposed

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Work performed from 8/18/81 to 9/15/81:

CONDITIONS OF APPROVAL, IF ANY:

Cleaned out to 8282'. Perforated from 7930'-94', 16 holes, .50" size. Set RBP at 8040'. Acidized perforations 7981'-94' with 2500 gallons 15% NE FE DS-30 acid. Reset RBP at 7940'. Acidized perforations 7930'-34' with 1200 gallons 15% NE FE DS-30 acid. Pulled RBP. Swabbed and tested with no shows. Set cement retainer at 7970'. Squeezed with 100 sacks Class "H" cement. Drilled out cement and cleaned back out to 8282'. Tested squeeze to 500#. Perforated from 8205'-13', 7 holes, .50" size. Acidized with 1400 gallons 15% MCA acid. Swabbed and tested with no shows. Set cement retainer at 8150'. Squeezed with 50 sacks Class "H" cement. Set cement retainer at 7880'. Squeezed with 100 sacks Class "H" cement. Drilled out cement to 7928' and pressured to 500#. Held pressure 5 minutes. Drilled cement and retainer to 8217'. Tested to 500#, held 5 minutes. Drilled cement to 8324', drilled float collar and cement to 8340'. Tested to 500#. Perforated from 8286'-8324', 10 holes, .67" size. Acidized with 4000 gallons MOD-101 acid. Swabbed and tested. Shut well in 8/15/81 waiting on orders.

18. I hereby certify that the information	tion above is true and complet	e to the best of my knowledge and belief.	
SIGNED H. F. Bu	with	TITLE Prod. Superintendent	DATE 9/16/81
	Orlg. Signed by		SEP 1 8 1981
APPROVED BY	Jerry Sexton	TITLE	DATE

Dist 1, Supr