

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

ANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

5a. Indicate Type of Lease

State ☒

Fed ☐

5. State Oil & Gas Lease No.

L6736

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole	7. Unit Agreement Name
2. Name of Operator Maguire Oil Company	8. Farm or Lease Name Union State
3. Address of Operator 4200 First National Bank Building Dallas, Texas 75202	9. Well No. 1
4. Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>4S</u> RANGE <u>32</u> NMPM.	10. Field and Pool, or Wildcat Peterson, Mississippi
15. Elevation (Show whether DF, RT, GR, etc.) 4522.8GR	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set CIBP@8200', dump 35' of cement on top of B.P.-GIH. cut of 4½ csg@ 7025'. Pull & lay down 4½" casing, GIH w/ 2-3/8" tbg to pump cement plug at top of 4½" csg, stub @ 7025', hit bridge @2280', drill out 25' bridge & wash to 7025'. Pump 100' plug 7025-6925', 4460-4360', 3200'-3100', 2050-1950' (in and out 8-5/8" intermediate casing)-Pump 10' plug top of 13-3/8" surface casing, cut off wellhead, weld on plate and set dry hole marker, move off equipment - will fill pits and level location as soon as possible.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED John C. Kelley TITLE Engineering Assistant DATE 11/16/81
APPROVED BY Ronald M. Coulter TITLE OIL & GAS INSPECTOR DATE NOV 8 1981

CONDITIONS OF APPROVAL, IF ANY: