

## IL CONSERVATION DIVISIO

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L6736	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole		7. Unit Agreement Name
2. Name of Operator Maguire Oil Company		8. Farm or Lease Name Union State
3. Address of Operator 4200 First National Bank Bldg., Dallas, Texas 75202		9. Well No. 1
4. Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>4S</u> RANGE <u>32</u> NMPM.		10. Field and Pool, or Wildcat Peterson, Mississippi
15. Elevation (Show whether DF, RT, GR, etc.) 4522.8 GR		12. County Roosevelt

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Intermediate Casing

Drilled 12 1/4" hole to 2006', shale & anhydrite, ran 46 joints 8 1/8" OD. 24# K-55 ST&C casing, set at 2006'. Cemented with 700 sxs Halliburton Lite, w/15% salt & 200 sxs class "C" w/2% cacl. Circulate 150 sxs. WOC 12 hrs, pressure up to 1000# no pressure drop.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____	TITLE <u>Engineering Assistant</u>	DATE <u>1/5/82</u>
<hr/>		
APPROVED BY <u>John C. Kelley</u>	TITLE _____	DATE <u>JAN 1 1982</u>
CONDITIONS OF APPROVAL, IF ANY:		