

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

5a. Indicate Type of Lease

State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tri-State Production & Supply Inc.	8. Farm or Lease Name Taylor
3. Address of Operator P.O. Box 1182, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER G 1980 FEET FROM THE North LINE AND 2130 FEET FROM East 28 TOWNSHIP 4 S RANGE 33 E N.M.P.M.	10. Field and Pool, or Wildcat Peterson Mississippi
15. Elevation (Show whether DF, RT, GR, etc.) G.L. 4319.0	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-16-81 Republic Rig # 6 spudded with 17 1/2 bit-drilled to 375'.

12-18-81 Set 9 joints 13 3/8 casing. 54# ST&C at 374' cement with 425 sacks class C with 2 % CACL and 1/4 celeflakes per sack. Pump plug to 334' with water. Circulated 25 sacks cement. W.O.C. 18 hours.

12-19-81 Weld on 13 3/8 X 900 series flange. Install 300# test B.O.P.. Test casing and B.O.P. to 1300 #. Held for 30 minutes. PSIG-ok Drill plug and cement from 330' to 375'-test shoe & casing to 800#-Drill ahead with 12 1/4 bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Subrey E. Lanyon TITLE Corporation President DATE _____

ORIGINAL SIGNED BY

JERRY SEXTON

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY, DISTRICT 1 SUPR.

MAY 4 1982