

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name VLS
9. Well No. 1
10. Field and Pool, or Wildcat S. Peterson (Penn)
12. County Roosevelt

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator H. L. Brown, Jr.
3. Address of Operator P. O. Box 2237, Midland, Texas 79702
4. Location of Well UNIT LETTER <u>P</u> , <u>660</u> FEET FROM THE <u>east</u> LINE AND <u>1300</u> FEET FROM THE <u>south</u> LINE, SECTION <u>11</u> TOWNSHIP <u>6S</u> RANGE <u>33E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4383.8

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:
REMEDIAL WORK <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>
ALTERING CASING <input type="checkbox"/>
PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 8 5/8" casing at 3397'. Ran 24 jts (1010.24) 32#/ft K-55, 58 jts (2388.43') 24#/ft K-55. Cmt w/1425 sx PaceSetter Lite w/7# salt P/S + 250 sx Class C w/1% calcium chloride. Plug down at 4:30 p.m. 4-27-82. Circulate 600 sx cement. Float held w/800 psi

Nipple up and test pipe and blind rams to 1500 psi 30 min.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>R.E. Loring</u>	TITLE <u>Drilling Superintendent</u>	DATE <u>4-28-82</u>
APPROVED BY <u>JERRY SEXTON</u>	TITLE <u>DISTRICT 1 SUPR.</u>	DATE <u>MAY 3 1982</u>

RECEIVED

APR 30 1982

O.C.D.
HOBBS OFFICE