

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tri-State Production & Supply Inc.	8. Farm or Lease Name Richardson
3. Address of Operator P.O. Box 1182, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM East THE LINE, SECTION 32 TOWNSHIP 4 S RANGE 33 E NMPM.	10. Field and Pool, or Wildcat Peterson Mississippi
15. Elevation (Show whether DF, RT, GR, etc.) G.L. 4399.9	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☒
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1-28-82 Republic Rig # 6 spudded with 17 1/2 bit-drilled to 375'
- 1-30-82 Set 9 joints 13 3/8 casing. 54 # L-55 ST&C at 374'. Cement with 425 sacks class C with 2 % CACL and 1/4 coleflakes per sack. Pump plug to 332' with water. Circulated 60 sacks cement to pit.
- 1-31-82 Weld on 13 3/8 X 900 series flange. Install 3000 # test B.O.P.. Test casing and B.O.P. to 1300#. Held for 30 minutes. PSIG-ok. Drill plug and cement from 330' to 375'- test shoe & casing to 800#-Drill ahead with 12 1/4 bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rubrey E. Canyon TITLE Corporation President DATE _____

ORIGINAL SIGNED BY
APPROVED BY JERRY SEXTON TITLE _____ DATE MAY 4 1982
CONDITIONS OF APPROVAL DISTRICT J. SUPR.