

NO. OF COPIES RECEIVED	
DISTRIBUTION	
AMT A FE	
ILC	
U.S.G.S.	
AND OFFICE	
PERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - C-103 FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Terra Resources, Inc.

Address of Operator

5 Greenway Plaza East, Suite 300, Houston, Tx 77046

Location of Well

UNIT LETTER M 990 FEET FROM THE South LINE AND 976 FEET FROM
THE West LINE, SECTION 18 TOWNSHIP 5S RANGE 34E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
4370.1 GL

5a. Indicate Type of Lease

State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name

B.F. Musick

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat

12. County

Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PLUG OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPS. ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-3/4" Casing Cemented @ 353', Cement Circulated To Surface
8-5/8" Casing Cemented @ 3,315', Cement Circulated To Surface

Drilled 7-7/8" hole to 8493, (TD) Granite Wash. Encountered no productive zones. Spotted 100' cement plug from 7970' to 8070' (Fusselman). Spotted 100' cement plug from 7790' to 7890' (Penn) Spotted 100' cement plug from 7160' to 7260' (Wolfcamp) Spotted 100' cement plug from 6620' to 6720' (Abo) Spotted 100' cement plug from 4547' to 4647' (Glorietta) Spotted 100' cement plug across bottom of 8-5/8" casing 3265'-3365' Spotted 100' cement plug in 8-5/8" casing from 1500' to 1600'. Set 10 sack cement plug at surface, installed prescribed 4" x 4" steel marker at surface. Subject well plugged and abandoned 12:00 Noon, Monday, May 3, 1982.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

WED.

TITLE

Basin Oil Consultants, Inc. DATE May 5, 1982

MOVED BY

TITLE

OIL & GAS INSPECTOR

DATE

CONDITIONS OF APPROVAL, IF ANY

RECEIVED

MAY 5 1982

O.C.D.
HOBBY OFFICE