NO. OF COPIES RECEIV		
DISTRIBUTION		Form C-103 Supersedes Old
SANTA FE		C-102 and C-103
FILE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
		P
U.S.G.S.		5a. Indicate Type of Lease
LAND OFFICE		State Fee X
OPERATOR		5. State Cil & Gas Lease No.
	SUNDRY NOTICES AND REPORTS ON WELLS HIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" IFORM C-101) FOR SUCH PROPOSALS.)	
1.	GAS	7. Unit Agreement Name
WELL L	WELL OTHER. Dry Hole	
2. Nume of Operator		8. Farm or Lease Name
Cities Servio	ce Company	May A
3. Address of Operator		9. Well No.
P.O. Box 1919	9 - Midland, Texas 79702	1
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER	1980 FEET FROM THE South LINE AND 660 FEET FROM	Wildcat
	1	AHHHHHHHH
THE West	LINE, SECTION 1 TOWNSHIP 2S RANGE 33E NMPM.	(1))))))))))))))))))))))))))))))))))))
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	//////////////////////////////////////	Roosevelt
16.	Check Appropriate Box To Indicate Nature of Notice, Report or Oth	
N		REPORT OF:
PERFORM REMEDIAL WOR	RK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	
	OTHER	
OTHER		
17. Describe Proposed work) SEE RULE 1	or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including	estimated date of starting any proposed
	anite Wash. This well was plugged and abandoned in the fo	ollowing manner:
		-
1. R	TH w/open ended DP and circulated hole w/mud laden fluid.	Spotted a 50 sack
C	ement plug @ 7357 - 7138', across the top of the Granite.	LDDP to 6415'.
2. S	potted a 50 sack cement plug @ 6415 - 6298', across the to	op of the Wolfcamp.
I	DDP to 5168'.	p or all norreally.
	potted a 50 sack cement plug 5168 - 5038', across the top	of the Tubb IDD
 t	\sim 3725'.	
	potted a 50 sack cement plug @ 3725 - 3598', across the to	n of the Claricta
. T	DDP to 2694'.	pp or the Groutera.
J. J. L	potted a 50 sack cement plug @ 2694 - 2568', across the to	pp of the San Andres and
	alf in and half out of the 8-5/8" casing shoe @ 2637'. If	DP to 1508'.
6. S	potted a 35 sack cement plug @ 1508 - 1375'. LDDP.	
7. D đ	umped a 10 sack cement surface plug @ 20 - 0'. Installed lesignate a plugged and abandoned location. Cleaned locati	a 4" dry hole marker to .on.
•		
Id. I hereby certify that	t the information above is true and complete to the best of my knowledge and belief.	
5D n	\mathbf{O}	

SIGNED tant	Reg. Opr. Mgr Prod.	DATE 1-12-83
APPROVED BY ACK Griffin	OIL & GAS INSPECTOR	JAN 6 - 1986
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED JAN 1 4 1983 NOBBS CA.