

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cities Service Company	8. Farm or Lease Name May A
3. Address of Operator P. O. Box 1919 - Midland, Texas 79702	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>1</u> TOWNSHIP <u>2S</u> RANGE <u>33E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4079' GR	12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2640' Dolo. and Anhy. Prep. to drill ahead. MIRU spud hole 11/26/82. Drilled to a TD of 350' in Red Beds. Ran and set 8 jts. (327') 13-3/8" 48# H-40 casing @ 340'. Cemented w/325 sacks Class C + 2% CaCl₂ & 1/4# Flocele. PD @ 0905 MST 11/27/82. Cement circulated. WOC 18 hours. Tested casing to 600# for 30 mins. - OK.

Drilled to a TD of 2640' in Dolomite and Anhydrite. Ran and set 60 jts (2622') of 8-5/8" 24# K55 casing @ 2637'. Cemented w/835 sacks of Lite w/1/4# Flocele and 6# salt/sack + 300 sacks Class C w/2% CaCl₂ cement. PD @ 1415 MST 12-4-82. Cement circ. WOC 18 hours. Tested casing to 800# for 30 mins. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Elmer Startz TITLE Reg. Opr. Mgr. Prod. DATE 12-10-82

ORIGINAL SIGNED BY
APPROVED BY JERRY SEXTON TITLE DISTRICT SUPER. DATE DEC 15 1982