

U.S. CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fed ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☐ OTHER- Dry Hole		7. Unit Agreement Name
1. Name of Operator Grand Banks Energy Company		8. Farm or Lease Name Craig
2. Address of Operator 302 Paragon Tower, 600 N. Marienfeld, Midland, TX 79701		9. Well No. 1
3. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM West LINE, SECTION 2 TOWNSHIP 5 S RANGE 32E NMPL.		10. Field and Pool, or Wildcat Stingray (Penn)
15. Elevation (Show whether DF, RT, GR, etc.) 4488 GL		12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☒
---	--	--	--

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugged and abandoned well as follows:



Ran 4 1/2" drill pipe to 8047'--Total depth. Circulated and conditioned hole w/10.8 lb./gal. mud. RU Dowell and spotted 8 Class "H", 15.8 lb./gal. cement plugs as follows:

- #1 - 35 sx. at 8,047 ft. - Total Depth
- #2 - 50 sx. at 7,140 ft. - Top of Wolfcamp
- #3 - 40 sx. at 6,525 ft. - Top of Abo
- #4 - 100 sx. at 4,450 ft. - Top of Glorieta
- #5 - 90 sx. at 3,045 ft. - Top of San Andres
- #6 - 85 sx. at 2,068 ft. - 50 ft. below 8 5/8" casing shoe
- #7 - 30 sx. at 437 ft. - 50 ft. below 12 3/4" casing shoe
- #8 - 10 sx. at surface

Welded cap on 8 5/8" casing and installed marker.

Well plugged and abandoned 11-30-82.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED 	TITLE VP - Drlg. & Production	DATE 1-04-83
APPROVED BY 	TITLE Geologist	DATE 12/28/83

CONDITIONS OF APPROVAL, IF ANY: