STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

DISTRIBUTION		
SANTA FE		
FILE		
U.S.O.S.	_	l
LAND OFFICE		
OPERATOR		

OIL CONSERVATION DIVISION

Form C-103 /

DISTRIBUTION	⊣	0, BOX 2088	Revised 10-1-78	
FILE	SANTA FE,	NEW MEXICO 87501	Sa. Indicate Type of Leuse	
U.1.0.1.			State Fee X	
LAND OFFICE			5. State Oil 6 Gas Lease No.	
OPERATOR				
		COLUMN TO LE		
SUND	RY NOTICES AND REPORT	SON WELLS		
USE "APPLICA	TION FOR PLANIT IFORM C-1011 F	DR SUCH PROPOSALB.	7. Unit Agreement Name	
61L TV 548				
weit X weit	OTHER.		B. Farm or Lease Name	
Name of Operator Gulf Energy Producing	Company		Taylor	
	Company		9. Well No.	
Address of Operator P.O. Box 32999 San	Antonio Texas 78	216	1	
	All College For		10. Field and Pool, or Wildcat	
Location of Well	`	owth 1080	Undesignated	
UNIT LETTERC	660 FEET FROM THE NO	orth LINE AND 1980 PEET FA		
	1.7	4.C 33V		
THE West LINE, SEC	TION IL TOWNSHIP	6S RANGE 33E NAME	~()	
······································	15. Elevation (Show w		12. County	
	15. Elevation (Show is	vacine of a No. On, every	Roosevelt	
6. Check	c Appropriate Box To Indic	cate Nature of Notice, Report or C	Other Data	
NOTICE OF	INTENTION TO:	SUBSEQUE	NT REPORT OF:	
PERFORM REMEDIAL WORK	PLUG AND ABANDO	ON REMEDIAL WORK	ALTERING CASING	
EMPORARILY ASANDON		COMMENCE DRILLING OPHS.	PLUG AND ASANDONMENT	
PULL OR ALTER CABING	CHANGE PLANS	CASING TEST AND CEMENT JOS X (Production)	
		OTHER		
OTHER				
	(6)	nent details, and give pertinent dates, includ	ing estimated date of starting any proposed	
7. Describe Proposed or Completed wprk/ SEE RULE 1 103.	Operations (Clearly state all pertin	ient details, and give personal design		
JANUARY 2, 1983;				
Pan 51 cacing as	follows: Halliburton	down jet guide shoe (.75'),	1 joint - $5\frac{1}{2}$ ", 17# K-55	
1TLC cea (34 98')	Halliburton diff. f	ill collar (1.50'), 65 jts	$-5\frac{1}{2}$ " 17# K-55 LT&C csg.	
(2403 67!) and 132) its 5%". 15.50# J	7-55 LT&C casing (5485.91').	Total pipe 7926.73'. Set	
casing at 7917' RK	KB. Installed centrali	zers at 7697', 7661', 7623"	, 7255', & 7222'.	
Cemented casing wi	ith 900 sacks Class "F	" cement containing 4/10% F	lalad 9 at 1.18 cu ft/sack	
and 14 8#/gal Pun	mped 1000 gal mud flus	sh ahead of slurry. Good ret	turns throughout job. Bumpe	
plug with 2700 psi	i – casing held. Relea	ased pressure and float held	I. Bumped plug at 4:27 PM,	
MST 1-2-83. ND BOI	P & set casing in full	tension.		
		_		
		•		
		•		
		he heat of my knowledge and belief.		
8. I hereby certify that the informat	Jon above to true and complete to the	Karen A. Omillian		
1		Regulatory Administrate	or page January 3, 198	
ICHER Daren U. C.	millian "	regulatory Administration	DATE SUITED STATE	
construct s			AAN 11 man	
PPRDYED BY SQUEST SE	ACTON		_ ···· JAN 11 1983	
ONDITIONS OF APPROVAL, IP A	が表音音が変		~ ~ /w	
ONDITIONS OF AFFRONCE, IF A				

RECEIVED

JAN 1 0 1983

HOZAS OFFICE.