

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANCTUARY	
FILE	
U.A.G.D.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Unit Agreement Name
3. Name of Operator Enserch Exploration, Inc.	4. Field or Lease Name Howard-Miller
5. Address of Operator 1230 River Bend Drive - Suite 136 - Dallas, Texas 75247	6. Well No. 1
7. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>8</u> TOWNSHIP <u>7-S</u> RANGE <u>32-E</u> AMPH.	8. Field and Pool, or Wildcat Wildcat
9. Elevation (Show whether DF, RT, GR, etc.) 4469.9' GR	10. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Operations to plug and abandon began on January 10, 1983 and ended January 10, 1983. The well was plugged by setting five Class H Neat cement plugs with a yield of 1.18 ft³/sk and slurry weight of 15.6 lb/gal. Total depth of the well was 4336 feet. The plugs were set as follows: (1) 4336' to 4236' with 35 sacks (2) 3343' to 3243' with 35 sacks; (3) 2500' to 2400' with 35 sacks; (4) 1650' to 1550' with 35 sacks; and (5) 30' to surface with 10 sacks. The following casing was left in the hole: Surface - 36 joints (1602'), 8-5/8", 24#, K-55, ST&C. A 10 lb/gal mud was used while plugging operations were in progress. All pits were filled and the location leveled clearing the site of all junk.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. H. Peoples TITLE Regional Drilling Manager DATE 1-19-83

APPROVED BY Ronald M. Littleberry TITLE OIL & GAS INSPECTOR DATE JUN 20 1983

CONDITIONS OF APPROVAL, IF ANY: