

UNIT **2 BOX 1980**
HOBBS, NEW MEXICO 88240
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Dry Hole

2. NAME OF OPERATOR

Celeste C. Grynberg

3. ADDRESS OF OPERATOR 79705

4000 N. Big Spring, Suite 109, Midland, TX

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE:

AT TOP PROD. INTERVAL: Non-Productive

AT TOTAL DEPTH: 4400'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☒

(other) _____

5. LEASE

USA-NM-12693

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Baliff Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Tomahawk, San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

17, T7S, R32E, NMPM

12. COUNTY OR PARISH

Roosevelt

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
GR 4470'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. 8 5/8" 24# casing @ 1700', cemented with 600 sacks of cement and circulated to the surface.
2. 5 1/2" 15.5# casing @ 4350', cemented with 250 sacks of 50-50, + 300 sacks, 50 sacks of Class "C". Cement top @ 3220' log.
3. Perforated 5 1/2" casing @ 4288' to 4317' (no production).
4. Propose to set the bridge plug @ 4150'. Spot 10 sacks cement on bridge plug.
5. Cut 5 1/2" casing @ 3050'. Spot 50' of cement above and below cut off.
- * → 6. Spot 50' above and below shoe of 8 5/8" casing @ 1700'. *Tag plug.*
7. Spot 10 sacks in the top of the 8 5/8" casing with dry hole marker.
8. Prepare to plug as soon as plan is approved.

* *100' cont. plug 2200' - 2400'*

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Peter W. Chester* TITLE Agent DATE January 4, 1985

APPROVED

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER TITLE _____ DATE _____

CONDITIONS OF APPROVAL IF ANY

JAN 10 1985



*See Instructions on Reverse Side

awc

Don't forget to