

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE
N. M. OIL CONS. COMMISSION
P. O. BOX 1900
HOBBS, NEW MEXICO 88240

Budget Bureau No. 1004-0135
Expires August 31, 1985
LEASE DESIGNATION AND SERIAL NO.

NM-12693

INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Celeste C. Grynberg	8. FARM OR LEASE NAME Baliff Federal
3. ADDRESS OF OPERATOR 5000 S. Quebec, Suite 500, Denver, CO 80237	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 330 FSL, 2310 FEL	10. FIELD AND POOL, OR WILDCAT Tomahawk, San Andres
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 17, T7S-R32E
15. ELEVATIONS (Show whether DF, RT, CR, etc.) 4470 GR	12. COUNTY OR PARISH Roosevelt
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud, run surface casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

--Spud 9 A.M., 6/30/84. Drill 40' of 16" hole, run 14" conductor pipe. Cement with Redi-Mix to surface. (Drilled with Rat Hole machine).

--Move in Capstar Rig #1 on 7/9/84, spud @ 11 P.M. Drilled 1700' of 12 1/4" hole, run 8 5/8" casing on 7/13/84 to 1700'. Cement with 600 sacks to surface, Class "C", 8% Gel. WOC 18 hrs.

--Drill out with 7 7/8" on 7/14/84.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling & Prod. Coordinator DATE 7/23/84

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL

ACCEPTED FOR RECORD

TITLE

DATE

JUL 26 1984

*See Instructions on Reverse Side