

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other Dry Hole  
well well

2. NAME OF OPERATOR

Celeste C. Grynberg

3. ADDRESS OF OPERATOR

79705

4000 N. Big Spring, Suite 109, Midland, TX

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE:

AT TOP PROD. INTERVAL: Non-Productive

AT TOTAL DEPTH: 4300'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other)

5. LEASE  
USA-NM-18846

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Celsius Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Tomahawk, San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 20, T7S, R32E, NMPM

12. COUNTY OR PARISH  
Roosevelt

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
4472' - 4473'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. 8 5/8" 24# casing @ 1717', cemented with 340 sacks. Cement was circulated to the surface.
2. 5 1/2" 15.5# casing @ 4300', cemented with 350 sacks. Cement top @ 3090' log.
3. Perforated 5 1/2" casing @ 4168' to 4212' (no production).
4. Propose to set bridge plug @ 4100'. Spot 10 sacks cement on the bridge plug.
- \* → 5. Cut 5 1/2" casing @ 3000'. Spot 50' of cement above and below cut off.
6. Spot 50' above and below shoe of 8 5/8" casing @ 1717'. *Tag plug*.
7. Spot 10 sacks in the top of the 8 5/8" casing with dry hole marker.
8. Prepare to plug as soon as plan is approved.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Agent

DATE

January 4, 1985

APPROVED

(This space for Federal or State office use)

APPROVED BY: PETER W. CHESTER  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JAN 16 1985