

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER H 1650 FEET FROM THE North LINE AND 990 FEET FROM
THE East LINE, SECTION 19 TOWNSHIP 7S RANGE 32E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Wilcox TS

9. Well No.

4

10. Field and Pool, or Whdcat

Tomahawk SA

15. Elevation (Show whether DF, RT, GR, etc.)

4467' GR

12. County

Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
FULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPS. ☒
CASING TEST AND CEMENT JOB ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 5:45 PM 7-25-84. Ran 41 jts of 8-5/8" 25# K-55 ST&C casing set 1665'. 1-Texas Pattern notched guide shoe set 1665'. Insert float set 1625'. Cemented w/500 sx Pacesetter Lite, 3% CaCl2, 1/4# celloseal/sack. Tailed in w/ 175 sx Class C 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 9:30 AM 7-27-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 9:30 PM 7-27-84. WOC 12 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature]

TITLE Production Supervisor

DATE 7-30-84

ORIGINAL FILED BY JANEY SEXTON

PROVED BY [Signature]

TITLE Production Supervisor

DATE AUG - 2 1984

CONDITIONS OF APPROVAL, IF ANY: