

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 53979

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 24

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 24, T-5-S, R-31-E

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR PARISH

13. STATE

Roosevelt

NM

15. DATE SPUDDED

16. DATE T.D. REACHED

17. DATE COMPL. (Ready to prod.)

18. ELEVATIONS (DF, RKB, RT, GB, ETC.)*

19. ELEV. CASINGHEAD

12-16-84

1-11-85

P & A on 1-15-85

4404' GR

No casinghead left

20. TOTAL DEPTH, MD & TVD

21. PLUG, BACK T.D., MD & TVD

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

7669' TD

24. PRODUCING INTERVAL(S). OF THIS COMPLETION-- TOP, BOTTOM, NAME (MD AND TVD)*

25. WAS DIRECTIONAL SURVEY MADE

Plugged and Abandoned @ 3:00 pm on 1-15-85 by Hondo Rig #7.

YES

26. TYPE ELECTRIC AND OTHER LOGS RUN

NGT/CNL-LDT/DLL

27. WAS WELL CORED

NO

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	61#	418'	17-1/2"	425 Class "C"	
9-5/8"	36#	3400'	12-1/4"	200 sx. Class "C"	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)

31. PERFORATION RECORD (Interval, size and number)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED

33.* PRODUCTION

DATE FIRST PRODUCTION PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump) WELL STATUS (Producing or shut-in)

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL--BBL.	GAS--MCF.	WATER--BBL.	GAS-OIL RATIO
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL--BBL.				

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

Deviation Surveys

36. I hereby certify that the foregoing and attached information is complete and correct as far as it goes and that it is based on all available records

SIGNED

TITLE

Engineer

DATE 2-4-85

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
San Andres	3842'	3873'	DST #1 Recovery: 100' Drilling Fluid Bottom Top IFP 83-83 41-41 ISIP 1484 1431 FFP 83-83 20-41 FSIP 1361 1308
Granite Wash	7609'	7669'	DST #2 Recovery: 35' Drilling Fluid Bottom Top IFP 229-167 102-61 ISIP 520 1021 FFP 229-125 82-61 FSIP 229 143

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Yates	1925'	
Queen	2523'	
San Andres	2949'	
Glorieta	4197'	
Tubb	5610'	
Drinkard	6000'	
Abo	6360'	
Wolfcamp	7068'	
Cisco	7396'	
Gr. Wash	7648'	

RECEIVED
FEB 11 1985
OFFICE