

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - P (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROMTHE West LINE, SECTION 33 TOWNSHIP 3S RANGE 30E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

4446' GR

12. County

Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐CHANGE PLANS ☐COMMENCE DRILLING OPNS. ☒PLUG AND ABANDONMENT ☐PULL OR ALTER CASING ☐CASING TEST AND CEMENT JOBS ☒OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 5:00 PM 3-14-85. Ran 9 joints 13-3/8" 54.5# J-55 ST&C casing set 362'. 1-guide shoe set 362'. Insert float set 325'. Cemented w/300 sx Class "C", 1/4# sxcelloseal with 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 3:15 AM 3-15-85. Bumped plug to 1000 psi, OK. Cement circulated 50 sacks to pit. WOC. Drilled out 8:00 PM 3-15-85. WOC 16 hrs and 45 minutes. Cut off and welded on flow nipple. Reduced hole to 11". Drilled plug and resumed drilling.

Ran 63 joints 8-5/8" 32# and 24# J-55 ST&C casing as follows: 13 joints 32# and 50 joints 24# casing set 2680'. 1-guide shoe set 2680'. Float set 2638'. Cemented w/875 sacks Pacesetter "C" Lite, 1/4#/sx celloseal and 5#/sx salt. Tailed in w/200 sx Class "C" + 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 11:00 AM 3-18-85. Bumped plug to 1000 psi, held okay. Cement circulated 50 sacks. WOC. Drilled out 2:30 PM 3-19-85. WOC 27 hrs and 30 minutes. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton
ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

TITLE Production SupervisorDATE 3-25-85

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

MAR 27 1985

RECEIVED

MAR 26 1985

OFFICE
OF THE
ATTORNEY GENERAL