

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-101  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tenneco Oil Company	8. Farm or Lease Name Carlock
3. Address of Operator 7990 IH 10 West, San Antonio, Tx 78230	9. Well No. 1
4. Location of Well UNIT LETTER <u>D</u> , <u>660</u> FEET FROM THE <u>north</u> LINE AND <u>660</u> FEET FROM THE <u>west</u> LINE, SECTION <u>7</u> TOWNSHIP <u>5S</u> RANGE <u>32E</u> NMPM.	10. Field and Pool, or Wildcat wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4520.6 GR	12. County Roosevelt

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPMS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 70 jts. of 8 5/8", 32#, K55, STC casing and set casing at 2920'. Cemented with 300 sxs of Dowell Hi-Early with 2% CaCl<sub>2</sub> and 925 sxs of Hi-Early II Lite with 10# salt and 1/4# Flo-cel. Plugged pump down with 1100 PSI on 11/12/85. Top of cement at surface. WOC 29.5 hours, tested casing and BOP to 3000 PSI. Held OK. Resumed operations.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Seay TITLE Drilling Engineer DATE 11/14/85  
APPROVED BY Oil & Gas Inspector TITLE \_\_\_\_\_ DATE NOV 18 1985  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

NOV 18 1985

O.C.D.  
HOBBS OFFICE