

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- DRY		7. Unit Agreement Name
2. Name of Operator BWAB INCORPORATED		8. Farm or Lease Name RADCLIFF 10-44
3. Address of Operator 1801 California Street, Suite 1000, Denver, CO 80202		9. Well No. #1
4. Location of Well UNIT LETTER <u>M</u> <u>330'</u> FEET FROM THE <u>South</u> LINE AND <u>330'</u> FEET FROM THE <u>West</u> LINE, SECTION <u>10</u> TOWNSHIP <u>6S</u> RANGE <u>35E</u> NMPM		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4,220' GR		12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Ran 9 jts of 13-3/8", 54.5#, J-55, ST&C csg & set @ 352'. Cemented with 350 sx Class "C" cement with 2% CaCl. Circ 175 sx cement.

Ran 81 jts of 8-5/8", 32# & 24# csg & set @ 3,395'. Cemented with 740 sx Class "C" Lite followed with 200 sx Class "C" with 2% CaCl. Did not circ. Ran temp survey to confirm top of cement. Mr. Sexton granted BWAB approval to drill ahead without squeezing or 1 inching backside. Top of cement from primary job @ 1,150' based on temp survey.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>John R. Keller</u>	TITLE <u>Production Superintendent</u>	DATE <u>04/16/86</u>
ORIGINAL SIGNED BY JERRY SEXTON DISTRICT 1 SUPERVISOR		DATE <u>APR 21 1986</u>
APPROVED BY:	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		