

CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LG 4034

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name None
2. Name of Operator Wood, McShane & Thams	8. Farm or Lease Name Newkumet & Green 16 State
3. Address of Operator P.O. Box 968, Monahans, Texas 79756	9. Well No. 1
4. Location of Well UNIT LETTER <u>N</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>16</u> TOWNSHIP <u>6 South</u> RANGE <u>33 East</u> NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 4405' GL	12. County Roosevelt

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Surface Casing- Set 8 5/8", 24# casing at 1990' from GL with 660 Sx Halliburton Light + 2 1/2# Salt/Sx; followed by 250 Sx Class "C" + 2% CaCL2. Cement top: Surface (Circulated 30 Sx to pit) Plug down at 6:45 am (CDT) 5-13-87. Pressure tested casing at 7:00 pm (CDT) 5-13-87 to 1000# with mud pump on drilling rig.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>John R. Ehlke</u>	TITLE <u>Drilling Foreman</u>	DATE <u>6-25-87</u>
APPROVED BY <u>Paul Kautz</u> Geologist	TITLE _____	DATE <u>JUL 1 1987</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED
JUN 30 1987
OCD
HOBBS OFFICE