

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
RECEIVED
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

NOV 27 '89

WELL API NO. 30-041-20846
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name MORRISON
8. Well No. 1
9. Pool name or Wildcat Tule-Pennsylvanian and Tule-Montoya

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
MARSHALL PIPE & SUPPLY COMPANY

3. Address of Operator 13423 Forestway Dr.
Dallas, Texas 75240

4. Well Location
Unit Letter A : 750 Feet From The North Line and 990 Feet From The East Line
Section 22 Township T2S Range R29E NMPM Roosevelt County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4339 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled out below 8-5/8" Casing October 30th, 1989, 8:00 P.M.
with 7-7/8" hole.

Drilled TOTAL DEPTH 7-7/8" Hole at 7170' November 16th, 1989.

Ran 205 Jts., 7166' of 5-1/2" 17# LT&C, Range 2 and 3, Seamless
Casing, drifted and tested to 5000#, and set at 7166'.

Cemented with 250 sacks "H" Cement, 2/10 of 1% CRF-3, 4# salt
per sack, and 500 gal. mud flush, displaced with KCL water.

Ran 15 centralizers and 40 scratchers. Scratched formation 1-1/2 hours
Ran float shoe, float collar and latch down plug at 7099'.

Good circulation through out. Plug down 10:30 P.M. November
17th, 1989. Top of cement calculated to be 6200'.

WAITING ON CEMENT

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J.W. Marshall TITLE Operator DATE 11-18-89

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____

CONDITIONS OF APPROVAL, IF ANY:

DEC 07 1989
DATE

RECEIVED

NOV 22 1989

OLD
HOMER GTHOB