

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOBBS OFFICE 000

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

P. O. Box 4395, Midland, Texas

11-27-62

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the..... **Cabot Corporation**

..... **Carper-State** Well No. **1** in **I**
 (Company or Operator) Lease (Unit)
NE 1/4 SE 1/4 of Sec. 20, T. 15-S, R. 32-E NMPM, Wildcat Pool
 (40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Well was drilled to 10,020' T. D. and 4-1/2" casing cemented at 9946' with 150 sacks of cement. Top of cement was 9455'. Casing was perforated in the interval 9879-86', and perforations treated with 3,000 gal. acid. Swabbing tests indicated a daily production rate of 20 b.o. and 24 b.w. A cast iron bridge plug was set at 9877', and casing perforated in the interval 9865'-76'. After treating perforations with 3,000 gal. acid, well swabbed 26 bbls. water per hour with only a slight trace of oil. To plug and abandon, a cement plug will be placed on bottom to cover the perforations, and then the 4-1/2" casing will be cut at approximately 9400'. A 20 sack cement plug will be placed in the top of the 4-1/2" casing stub and 20 sacks will be placed at the bottom of the 8-5/8" intermediate casing. The 8-5/8" casing will be cut and pulled from approximately 2,000', and a 20 sack cement plug placed in the top of the 8-5/8" casing stub. The surface will be plugged with 20 sacks of cement in the top of the surface casing with a steel plate welded on top.

Approved....., 19.....

Except as follows:

1st plug to be at least 25' above top of 4-1/2" casing
2nd plug to be at least 25' above top of 8-5/8" casing
3rd plug to be at least 25' above top of 8-5/8" casing

Approved

OIL CONSERVATION COMMISSION

By.....

Title.....

Cabot Corporation

Company or Operator

By..... **Percy C. O'Quinn**Position..... **Dist. Prod. Sup't.**

Send Communications regarding well to:

Name..... **Percy C. O'Quinn**Address..... **Box 4395, Midland, Texas**

