

## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

HOURS OFFICE OCC

## **MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will 60 returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

	Indicate	Nature of Notice by Checkin	g Below	
ce of Intention hange Plans		of Intention to krily Abandon Well	Notice of Intention to Drill Deeper	
ce of Intention lug Well	Notice o	of Intention Back	Notice of Intention to Set Liner	
ice of Intention Queeze	Notice o to Acidiz	of Intention Er	Notice of Intention to Shoot (Nitro)	
rice of Intention Gun Perforate	Notice o	F Intention	Notice of Intention (Other)	
. CONSERVATION COMMITA FE, NEW MEXICO	<b>MISSION</b>	Midland, Texas	January 25, 1963	
tlemen:				
Following is a Notice of Int	tention to do certain wor	rk as described below at the		
DOB Oil Prope	rties. Inc.	Champlin-State	Well Noin	E (Unit)
W 1/4 NW 1/4 of S	iec. 27 T 1	5-8 8 32-E W	PM, North Anderson Ranch	(OMIL)
Propose to p	(FOLLOW INSTRUC	LS OF PROPOSED PLANTIONS IN THE RULES ANd that was set on the set	ND REGULATIONS)  Sop of 8-5/8" stub at 1179"	· .
then set 25 s then set a 25 casing at 34	ull 8-5/8" casts ack coment plus sack coment p	ng that was set on t ig in and out of 8-5, lug in and out of the 8 sack coment plug	op of 8-5/8" stub at 1179' /8" stub via drill pipe, e bottern of the surface at the surface. Weld	•
then set 25 s then set a 25 casing at 342 plate on suri	ull 8-5/8" casts ack coment plus sack coment p	ng that was set on t ig in and out of 8-5, bug in and out of th 8 sack coment plug " pips welded vertice	nd regulations)  top of 8-5/8" stub at 1179'  /8" stub via drill pipe,  • bottern of the surface	•
then set 25 s then set a 25 casing at 342 plate on suri	ull 8-5/8" casts ack coment plus sack coment plus to the set a 1 lace 4-1/2" x 4	ng that was set on t ig in and out of 8-5, bug in and out of th 8 sack coment plug " pips welded vertice	op of 8-5/8" stub at 1179' /8" stub via drill pipe, e bottern of the surface at the surface. Weld	•
then set 25 s then set a 25 casing at 342 plate on suri	ull 8-5/8" casts ack coment plus sack coment plus to the set a 1 lace 4-1/2" x 4	ng that was set on t ig in and out of 8-5, bug in and out of th 8 sack coment plug " pips welded vertice	op of 8-5/8" stub at 1179' /8" stub via drill pipe, e bottern of the surface at the surface. Weld	•
then set 25 s then set a 25 casing at 342 plate on suri	ull 8-5/8" casts ack coment plus sack coment plus to the set a 1 lace 4-1/2" x 4	ng that was set on t ig in and out of 8-5, bug in and out of th 8 sack coment plug " pips welded vertice	op of 8-5/8" stub at 1179' /8" stub via drill pipe, e bottern of the surface at the surface. Weld	
then set 25 s then set a 25 casing at 342 plate on suri	ull 8-5/8" casts ack coment plus sack coment plus to the set a 1 lace 4-1/2" x 4	ng that was set on t ig in and out of 8-5, bug in and out of th 8 sack coment plug " pips welded vertice	op of 8-5/8" stub at 1179' /8" stub via drill pipe, e bottern of the surface at the surface. Weld	
then set 25 s then set a 25 casing at 34i plate on suri operator, we	ull 8-5/8" casts ack coment plus sack coment plus to the set a 1 lace 4-1/2" x 4	ng that was set on t ig in and out of 8-5, bug in and out of the 8 sack coment plug " pips welded verti- ation.	op of 8-5/8" stub at 1179' /8" stub via drill pipe, e bottern of the surface at the surface. Weld	•
then set 25 s then set a 25 casing at 342 plate on suri	ull 8-5/8" casts ack coment plus sack coment plus to the set a 1 lace 4-1/2" x 4	ng that was set on t ig in and out of 8-5, bug in and out of the 8 sack coment plug " pips welded verti- ation.	top of 8-5/8" stub at 1179' /8" stub via drill pipe, e bottom of the surface at the surface. Weld cally on top with name of	•
then set 25 a then set a 25 casing at 34i plate on suri operator, we proved	(FOLLOW INSTRUCTURE) 8-5/8" casis sack coment plus sack c	ng that was set on to g in and out of 8-5, bug in and out of the sack coment plug "pipe welded vertication.  By	cop of 8-5/8" stub at 1179' /8" stub via drill pipe, e bottom of the surface at the surface. Weld cally on top with name of	
then set 25 s then set a 25 casing at 34i plate on suri operator, we every served	(FOLLOW INSTRUCTURE) 8-5/8" casis sack coment plus sack c	ng that was set on to g in and out of 8-5, ling in and out of the sack coment plug "pipe welded vertication.  By Position A	op of 8-5/8" stub at 1179' /8" stub via drill pipe, bottom of the surface at the surface. Weld cally on top with name of	

811 First National Bank Building

Midland, Texas