

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

December 31, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Amerada Petroleum Corporation State CNA Well No. 1 in the

SE₁ SE₁ Company or Operator of Sec. 33, T. 15S, R. 32E, N. M. P. M.,
Wildcat Field, Lea County.

The dates of this work were as follows: December 30, 1948

Notice of intention to do the work was ~~(crossed out)~~ submitted on Form C-102 on December 30, 1948 19
 and approval of the proposed plan was ~~(crossed out)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

5025' Total Depth, Lime. Ran Schlumberger Survey & their Gamma Ray. Ran Drill pipe open ended and spotted 20 sx Common cement from 5025'- 4951' and flushed with 38 bbls. mud, Laid down drill pipe and spotted 20 sx. common cement from 1390'- 1316', flushed with 11 bbls. mud, Laid down drill pipe and spotted 10 sx common cement from 290' - 270' and flushed with 2 bbls. mud, laid down drill pipe and spotted 10 sx. common cement in 10-3/4" casing from top down 19'. Put 4" pipe 6' high in center of top plug. Finished at 10:30 P.M. 12-30-48.

Witnessed by D.F. Furse Amerada Petroleum Corporation Foreman
 Name Company Title
 Subscribed and sworn before me this
31st. day of December 1948
Will Hildebrand
 Notary Public
 I hereby swear or affirm that the information given above is true and correct
 Name [Signature]
 Position Foreman
 Representing Amerada Petroleum Corporation
 Company or Operator
 My commission expires _____ Address Drawer D, Monument, New Mexico

Remarks:

DEC 31 1948
 5115

[Signature]
 Name
 Title