

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
E-8974

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Union Oil Company of California	8. Farm or Lease Name No. Anderson Ranch Unit
3. Address of Operator P. O. Box 671 - Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER C, 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 33 TOWNSHIP 15 South RANGE 32 East N.M.P.M.	10. Field and Pool, or Wildcat Anderson Ranch Wolfcamp
15. Elevation (Show whether DF, RT, GR, etc.) 4318' D.F.	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

Spot Plug No. 1 from 10,025' to 9,700' w/ 50 sx Class "H" cement.  
Free-Point 5-1/2" OD Casing and cut off (at approximately 7,000').  
Spot Plug No. 2 from 7,050' to 6,950' inside 5-1/2" OD Casing and 7-7/8" open hole w/ 50 sx Class "H" cement.  
Spot Plug No. 3 from 5,700' to 5,600' in 7-7/8" open hole w/ 50 sx Class "H" cement.  
Spot Plug No. 4 from 4,196' to 4,096' in 7-7/8" open hole and 8-5/8" OD Casing w/ 50 sx Class "H" cement.  
Free-Point 8-5/8" OD Casing and cut off (at approximately 2,000').  
Spot Plug No. 5 from 2,050' to 1,950' inside 8-5/8" OD Casing and 11" open hole w/ 45 sx Class "H" cement.  
Spot Plug No. 6 from 642' to 542' in 11" open hole and 11-3/4" OD Casing w/ 55 sx Class "H" cement.  
Spot Plug No. 7 from 10' to surface w/ 10 sx Class "H" cement.  
Heavy mud laden fluid (at least 9.5 ppg) to be placed between plugs.  
Weld 1/2" steel plate on 11-3/4" OD Casing, and weld pipe marker, all according to N.M.O.C.C. Rules and Regulations.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J.R. Hughes TITLE District Drilling Supt. DATE January 2, 1975

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: