## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Report by Checking B	elow	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)	
	November 8, 1954	Habbs, Ne	w Mexico
Following is a report on the work of	lone and the results obtained under the heading		acei
Culf Oil Corper	ration	Les State "CR"	
(company or open	<b>18. Co</b> , Well No <b>1</b>	(Lease)	
	rson Ranch-Wolfcamp Pool	Lea	County.
	November 3-6, 1954		
	(was not) submitted on Form C-102 on	(Cross out incorrect words)	, 19
and approval of the proposed plan (****)	(was not) obtained.		
DETAIL	ED ACCOUNT OF WORK DONE AND RESU	II TE ABTAINED	
Ran 244 Jts and cut jt casing. Set and comented Maximum pressure 600#. Jo	(9857') 5-1/2" OD 17#, and 15.5 at 9874' with 300 sacks 4% Gel be complete by Howco 6:45AM 11-3 curs, tested 5-1/2" casing with are. Drilled cement plug from Ne drop in pressure.	0# Gr N-80 and J-55 SS cement. Plug at 9788'. -54. 1000# for 30 minutes. 9788' to 9855'. Tested	l
Ran 244 Jts and cut jt casing. Set and comented Maximum pressure 600#. Jo  After waiting over 30 h There was no drep in press with 1000# for 30 minutes.	(9857') 5-1/2" OD 17#, and 15.5 at 9874' with 300 sacks 4% Gel b complete by Howco 6:45AM 11-3 cours, tested 5-1/2" casing with sure. Drilled cement plug from No drop in pressure.  Gulf Oil Corporation (Company)	O# Gr N-80 and J-55 SS cement. Plug at 9788' -54.  1000# for 30 minutes. 9788' to 9855'. Tested	ena.n
Ran 244 Jts and cut jt casing. Set and comented Maximum pressure 600#. Jo  After waiting over 30 h There was no drep in press with 1000# for 30 minutes.	(9857') 5-1/2" OD 17#, and 15.5 at 9874' with 300 sacks 4% Gel b complete by Howco 6:45AM 11-3 curs, tested 5-1/2" casing with are. Drilled cement plug from No drop in pressure.  Gulf Oil Corporation (Company)	O# Gr N-80 and J-55 SS cement. Plug at 9788' -54.  1000# for 30 minutes. 9788' to 9855'. Tested  at the information given above is true	ena.n
Ran 244 Jts and cut jt sasing. Set and comented Maximum pressure 600#. Jo  After waiting over 30 h There was no drep in press with 1000# fer 30 minutes.  Witnessed by R. S. Rugi (Name)	(9857') 5-1/2" OD 17#, and 15.5 at 9874' with 300 sacks 4% Gel b complete by Howco 6:45AM 11-3 curs, tested 5-1/2" casing with are. Drilled cement plug from Ne drop in pressure.  Calf Oil Corporation (Company)  I hereby certify the to the best of my Name	O# Gr N-80 and J-55 SS cement. Plug at 9788' -54.  1000# for 30 minutes. 9788' to 9855'. Tested  at the information given above is truknowledge.	ena.n
Ran 244 Jts and cut jt casing. Set and comented Maximum pressure 600#. Jo  After waiting over 30 h There was no drep in press with 1000# for 30 minutes.  Witnessed by R. S. Rung (Name)	(9857') 5-1/2" OD 17#, and 15.5 at 9874' with 300 sacks 4% Gel b complete by Howco 6:45AM 11-3 curs, tested 5-1/2" casing with are. Drilled cement plug from No drop in pressure.  Company  I hereby certify the to the best of my  Name  Position	O# Gr N-80 and J-55 SS cement. Plug at 9788' -54.  1000# for 30 minutes. 9788' to 9855'. Tested  at the information given above is true	ic and complete