

COPIES RECEIVED		
TRIBUTION		
FE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-3510
7. Unit Agreement Name
8. Farm or Lease Name Lea CR State
9. Well No. 2
10. Field and Pool, or Wildcat Undesignated
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Gulf Oil Corporation
3. Address of Operator Box 670, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER <u>0</u> , <u>3300</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>2</u> TOWNSHIP <u>16-S</u> RANGE <u>32-E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 4271' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11,363' TD.

Loaded hole with mud. Set CI BP at 9500' and capped with 6 sacks of cement. Cut and recovered 5-1/2" casing from 5990'. Spotted 21 sack cement plug from 5940' to 6040', across 5-1/2" casing stub at 5990'; 30 sack cement plug from 5600' to 5700', across top of Glorieta at 5650'; 34 sack cement plug from 4140' to 4240'; across 9-5/8" shoe at 4190' and 19 sack cement plug from 50' to surface. Installed dry hole marker and cleaned location. Plugged and abandoned March 25, 1974. Will advise when location is ready for inspection.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>B. J. Lambert</u>	TITLE <u>Area Engineer</u>	DATE <u>March 25, 1974</u>
APPROVED BY _____	TITLE <u>Joe D. Ramsey</u>	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		

Dist. I, Supv.