

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO.

30-025-00381

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

022351

7. Lease Name or Unit Agreement Name:

TexMack 6 State

8. Well No.

#1

9. Pool name or Wildcat Anderson Ranchwest (Penn)

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☐ Other ☐

2. Name of Operator

Chevron-Texaco, Corp.

3. Address of Operator

P. O. Box 3109, Midland, TX 79705

4. Well Location

Unit Letter K : 3228 feet from the North line and 1987 feet from the West line

Section 6

Township 16S Range 32E NMPM Lea County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

- Set 7" CIBP on top of Pkr @ 11,670' (Penn) spot 40 sx plug 11,670'-11,500' Tag @ 11,401'
- Displace hole w/MLF 9.5# Brine 25# gel P/BBL
- Spot 40 sx plug 8200'-8000'
- Spot 40 sx plug 5100'-4900' (Csg Patch)
- Spot 40 sx plug 4200'-4000' (9 5/8" shoe) Tag @ 3933'
- Spot 40 sx plug 2900'-2700' (Yates B-Salt)
- Spot 40 sx plug 1300'-1100' (T-Salt)
- Perf 6 holes @ 700', Sqz w/125 sx 700'-500' (13 3/8" shoe) Tag @ 483'
- Circ cmt 30' to surf w/10 sx. Install dry hole marker. 11/15/01

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE MANAGER

DATE 11-15-01

Type or print name

Jimmy BAGLEY

(This space for State use)

Telephone No. 915 683-4996

APPROVED BY

Billy E. Pruchman

TITLE

COMPLIANCE OFFICER

DATE JUN 26 2002

Conditions of approval, if any:

GWW