

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

(Place)

Sept. 24, 1957

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....West Anderson Ranch Unit

Continental Oil Company

(Company or Operator)

Well No. 1 in K

(Unit)

NE 1/4 SW 1/4 of Sec. 6, T. 16S, R. 32E, NMPM, West Anderson Ranch Penn Pool

(40-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Permission was granted on 9-23-57 to plug and abandon the above well. We wish to change the procedure as follows:

1. Set cast iron bridge plug with one sack cement at 11,000 above perforations, 12,512-30 and 12,542-50.
2. Set cast iron bridge plug with one sack cement at 10,000 above perforations, 10,920-80.
3. Set cement plug across perforations 9,030-9,080.
4. Pull approximately 6,000' of 7" casing and set 100' cement plug across the top of the 7" casing.
5. Set 100' cement plug across bottom of the 9 5/8" casing at 4,095'.
6. Set 50' cement plug at surface.
7. Erect steel marker at surface and restore location to original level.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....

Continental Oil Company

Company or Operator

By.....

Position..... District Engineer

Send Communications regarding well to:

Name..... Continental Oil Company

Address..... Box 427, Hobbs, New Mexico