

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0069

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Robinson Unit

8. FARM OR LEASE NAME

Robinson Unit Tr. 2-31

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Malj. Grayb. S.A.

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

31-16S-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

1.

OIL  
WELL ☐

GAS  
WELL ☐

OTHER

Injection Well

2. NAME OF OPERATOR

Aztec Oil & Gas Company

3. ADDRESS OF OPERATOR

P.O. Box 837, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

Unit Letter F, 1980'/NL 2240'/WL, Sec. 31-16S-32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4112 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON\* ☒

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

It is proposed to plug and abandon in the following manner: No casing will be pulled.

1. Set 100' cement plug above perforations at 3800'-3867' (Overall)

2. Fill casing with mud

3. Set 100' cement plug at 980' (Top Salt)

4. Set 10' plug at surface with marker

5. Clear, level and clean location.

Note: It may be necessary to set bridge plug above perfs. w/35' cement plug instead of 100' cement plug.

AMENDMENT: 1. Set additional 25 sack plug inside 4 1/2" casing in interval 2300-2500 feet.

2. If no 4 1/2" casing is pulled, perforate at 900 feet and place 25 sacks cement through perforations and leave 25 sack plug inside casing in interval 700-900 feet.

18. I hereby certify that the foregoing is true and correct.

SIGNED

*Arthur R. Brown*

TITLE District Superintendent

DATE 10/7/74

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED  
AS AMENDED  
NOV 29 1974

ARTHUR R. BROWN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side