

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR NOTICES TO OWNERS OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL OR TO PLUG BACK TO A DIFFERENT RESERVOIR.)		5a. Indicate Type of Lease State ☒ Fee ☐ 5. State Oil & Gas Lease No. E-7177
1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER- Junked hole - P&A	7. Unit Agreement Name Robinson Unit	
2. Name of Operator Southland Royalty Company	8. Farm or Lease Name Robinson Unit TR 5	
3. Address of Operator 1100 Wall Towers West, Midland, TX 79701	9. Well No. Sec 31 10	
4. Location of Well UNIT LETTER J 1880 FEET FROM THE South LINE AND 1980 FEET FROM East THE LINE, SECTION 31 TOWNSHIP 16-S RANGE 32-E	10. Field and Pool, or Wildcat Undesignated (Queen)	
15. Elevation (Show whether DF, RT, GR, etc.) 4106' GR	12. County Lea	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ TEMPERARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐ REMEDIAL WORK ☐ COMMENCE DRILLING OPS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER Report of attempted re-entry ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-27-78 RUPU. GIH 9 7/8" bit drill out surface plug.

7-28-78 Drill cement to top of old 5 1/2" csg @ 221'. Ran tie in string of 5 1/2", tag old stub @ 221'.

7-29-78 Ran 4 3/4" bit inside 5 1/2", drill cement 660-815'.

7-30-78 Drill cement 815-819'. Impression block indicate damaged 5 1/2" csg @ 819', drill to 824'.

7-31-78 SI

8-1-78 Ran mill. Mill through tite spot @ 818', continue in hole to 3112'.

8-2-78 Ran string mill. Mill tite csg 815-830'.

8-3-78 Ran Halliburton "Casing Alignment Tool" and cement retainer 810-832' w/ T/cement retainer @ 810'. Cement w/ 350 sx Class "C" w/2% C.C., squeeze to 750#.

8-4-78 Drill out cement retainer @ 810', drill to 840'. Started getting formation.

8-5-78 Drill red bed, shale to 916', bit outside 5 1/2" csg.
Spot 30 sx cement 716-816'
15 sx cement 167-220'
10 sx cement Surface
Install dry hole maker. WELL PLUGGED & ABANDONED.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: C. Harney Carr TITLE: District Engineer DATE: 8-7-78

APPROVED BY: Edd J. ... TITLE: OIL & GAS INSPECTOR DATE: ...

CONDITIONS OF APPROVAL, IF ANY: