

FORMATION RECORD

	FROM	TO	THICKNESS IN FEET	FORMATION
5/21	0	60	60	Caliche & Sand
	60	180	120	Sand
	180	590	410	Red Bed
	590	1090	500	Red Bed and Shells
	1090	1175	85	Red Bed
5/28	1175	1235	60	Anhydrite 1194' 8-5/8" Casing cemented 50 sax Moved out rotary-rigging up spudder.
6/9	1235	1295	60	Red Rock
	1295	1410	115	Red Rock, Broken Anhyd & Salt
	1410	2070	660	Salt
	2070	2115	45	Salt & Potash
	2115	2235	120	Salt
	2235	2255	20	Anhyd
	2255	2300	45	Red Rock
	2300	2330	30	Salt
	2330	2405	75	Anhyd
	2405	2450	45	Anhyd & R Rock
	2450	2475	25	Red Rock
	2475	2585	110	Anhydrite
	2585	2590	5	Sand
	2590	3350	760	Anhydrite
6.28	3350	3375	25	Anhyd & Sand (Water 65-75
	3375	3390	15	Anhydrite Ran 7" Drilling string pipe
	3390	3437	47	Anhyd. Water not shut off-cemented 8" 20 sax
	3437	3795	358	Anhydrite
	3795	3805	10	Lime
	3805	3825	20	Anhydrite
7/25	3825	3975	150	Lime - Knocked off - pulled 7" Casing. Ran 5-1/2" Casing 3970 Cemented 100 sax.
7/28	3970	3975		Tested for shutoff 2 hrs after drilling plug.
	3970	3987	12	Lime
	3987	3990	3	Blue Shale
	3990	3995	5	Lime Free Oil - little gas
	3995	4000	5	Sandy lime
	4000	4030	30	Lime
	4030	4033	3	Gray Lime Increase Oil
	4033	4036	3	Lime
	4036	4040	4	Gray Lime
	4040	4074	34	Gray lime
	4074	4089	15	Lime
	4089	4094	5	Sandy Lime Increase in oil
	4094	4135	41	Lime Increase Oil and Gas..
8/22	4135	4140TD	5	Hard Lime TD..