

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
verse side)1*
re-Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 063867

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Harrison

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

M11janar

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec 3, T17S, R32E
NM PM

12. COUNTY OR PARISH

Lea

13. STATE

N. Mex.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Cima Capital Inc. (NSL)

3. ADDRESS OF OPERATOR

211 N. Ervay, Rm. 1320, Dallas, Texas 75201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1986' FN & 1990' FW

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4291 GR.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well drilled & completed in 1949

2 5/8 Csg. 1290' cemented w 50 sacks; 3 1/2" Csg. 3990' cemented w 100 sacks open hole 3990' - 4340'

Well to be P & A in Oct. or Nov. 1978.

Casing will be filled w 9-10 lb mud, and cement plugs will be placed as listed below:

1st 3950' - 4150' 25 sacks in 3 1/2" Csg. & open hole -

2nd 2500' - 2700' 25 sacks in 3 1/2" Csg.

3rd 1130' - 1350' 25 sacks in 3 1/2" & 8 5/8" Csg.

4th 0' - 15' 5 sacks in 8 5/8" Csg.

Marker to be placed in surface plug -

- AMENDMENT: 1. 5 1/2" casing should be cut and pulled from below 1350 feet before placing plug #3 above.
2. If no 8-5/8" casing is pulled, pipe should be perforated at 350 feet and a 100-foot plug placed outside and inside 8-5/8" casing through interval 250 to 350 feet.
3. Surface plug should be a minimum 20 feet in length.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Vice President

DATE

9-26-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

PROVED
AS AMENDED

NOV 3 1975

ARTHUR R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

RECEIVED
FEB 14 1975
U. S. GOVERNMENT PRINTING OFFICE