

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTINUE IN REVERSE
OFFICE FILE NUMBER
OF COPIES REQUIRED
(Other instructions on reverse side)

RM Rowell District
Modified Form No.
1160-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for each proposal.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		4. LEASE DESIGNATION AND SERIAL NO. LC-059576	
2. NAME OF OPERATOR The Wiser Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR PO Box 1412, Artesia, NM 88211-1412		7. UNIT AGREEMENT NAME Maljamar Grayburg Unit	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL & 1905' FEL Unit O		8. FARM OR LEASE NAME	
14. PERMIT NO. API #3002500445		9. WELL NO. 12	
15. ELEVATIONS (Show whether OF, RT, GR, etc.) 4284' GR		10. FIELD AND POOL, OR WILDCAT Maljamar Grayburg San Andres	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 3-T17S-R32E	
		12. COUNTY OR PARISH Lea	
		13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
ABANDON OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
ABANDON OR ACIDIZING
(Other) Deepen

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled 4-3/4" hole from 4226-4415'. Ran CBL & Casing Inspection Log. Top of cement @ 3040' from CBL. Ran 4" liner @ set @ 4415'. Top of liner @ 3852'. Cement liner w/90 sx Premium Plus cmt w/additives. Ran CBL - showed top of cement @ 4055. Perf'd 4" liner @ 4030'. Squeeze w/25 sx cmt w/additives. Drilled cmt 3800-3852' (top of liner). Cleaned out to 4410'. Perf'd the following intervals: 4048, 53, 54, 55, 58, 83, 84, 85, 87, 88, 99, 4105, 09, 27, 36, 37, 39, 73, 74, 75, 76, 83, 93, 97, 4201, 07, 09, 61, 62, 63, 4341, 42, 45, 46, 47 (35 holes). Acidized perfs 4048-4347 w/3000 gal 15% NEFE acid. Set 5-1/2" pkr @ 3813'. Tested annulus to 400 psi for 15 minutes, held good.

ACCEPTED FOR REC
ORIG. SCDJ DAVID R. GLASS
2 1993
CARLSBAD, NEW MEXICO

NOV 3 11 32 AM '93
CARLSBAD AREA OFFICE

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED Perry L. Hughes TITLE Agent

DATE 10/28/93

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side