(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERI GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS

SOUDKI MOIIS	The second secon
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY URE OF REPORT, NOTICE, OR OTHER DATA)
	June 11 , 19 5

						June 1	.1	., 19.34
Well No9 is	located	30 ft. f	$\operatorname{rom} \left\{ egin{array}{c} lacksquare \ S \end{array} ight\} \operatorname{line}$	and 990	ft. fron	n (E) lir	ne of sec	c. <u>3</u>
(% Sec. and Sec. No.)	3	Twp.)	(Range)	(A)	Meridian)	0x1 c 0		
Robert s			ty or Subdivision)			(State or Te	rritory)	

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) Plan to drill well as follows; set 8 5/8 pipe about 1300 feet cement

the pipe with 50 macks of cement.

set 7" pipe through the red sand about 3500 feet. Full the 7" pipe after the 52 pipe has been set.

et 5% alpe at 4050 feet cement the pipe with 100 secks of cement preceded by mud.

The well/be drilled with rotary tools to 1300 feet and with cable tools to about 4200 feet.

	that this plan of work must receive approval in writing by	the Geological Survey before oper	ations may be commenced.			
I understand	that this plan of work must receive approval in writing by					
Address	wallamar, New Yex					
		By 10 1- 10 yan				
		litle				