

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fc, New Mexico

WELL RECORD TO 10 10

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations

# 10	Lea Course Cours	ectionling Commenter of Drilling	Rober O 3 aced Contract ea level a	if S 11-8-58 Th tor Ho t Top of Tubir	South itate Land the Oil and omas Drilli bbs, New He	Pool,	660 was Completed.	feet from	West
Roberts Fool,	Cou dest from liest 11-29-58	is	Rober O 3 aced Contract ea level a	if S 11-8-58 Th tor Ho t Top of Tubir	South itate Land the Oil and omas Drilli bbs, New He	Pool,	660 was Completed.	feet from	West
is 660 feet from line and 660 feet from 3 If State Land the Oil and Gas Lesse No. is 11-8-58 ng Commenced 11-8-58 ng Commenced Thomas Drilling Company Hobbs, New Hexico 11-29-5 to of Drilling Contractor Hobbs, New Hexico 168 The information given is to 19 19 OIL SANDS OR ZONES 1, from 3952 3962 No. 4, from 1208 1, from 3972 3990 No. 5, from 10 10 10 10 10 10 10 1	11-29-58 apleted 11-29-58 apleted 19	ng Commen e of Drilling	Contract	If S 11-8-58 The tor Ho t Top of Tubir	South State Land the Oil and CORRS Drilli bbs, New Me	d Gas Lease No.	660 was Completed.	11-29-58	West
If State Land the Oil and Gas Lesse No. is	11-29-58 spleted	ng Commen e of Drilling	Contract	If S 11-8-58 The tor Ho t Top of Tubir	comes Drilli bbs, New He	d Gas Lease No.: 19 Drilling ng Compan xico	was Completed.	11-29-58	3 , 19
Thomas Drilling Company of Drilling Contractor. Hobbs, New Mexico ess. 4168 tion above sea level at Top of Tubing Head The information given is to 01L SANDS OR ZONES 1, from 3952	The information given is to be kept confidential to	of Drilling	Contract	Theorem Ho	omas Drilli bbs, New Me	ng Compan	was Completed.	11-27-70	, 19
Thomas Drilling Company Hobbs, New Mexico ation above sea level at Top of Tubing Head	The information given is to be kept confidential to	e of Drilling	Contract	t Top of Tubir	omas Drilli bbs, New Me	ng Compan xico	<u></u>	***************************************	
168	4208 4222 to to to to to feet.	ation above s	ea level a	t Top of Tubir	ng Head	1.720		,	
OIL SANDS OR ZONES 3952 3962 No. 4, from 4208 No. 5, from to 4088 No. 6, from to No. 6, from to Market Sands IMPORTANT WATER SANDS Ide data on rate of water inflow and elevation to which water rose in hole. 3330 1, from to feet.	4208 4222		3952				I HE IIII	ormation given is to b	e kept confidential
3952 3962 No. 4, from to	to	, from	3952						
3972 3990 No. 5, from to 4088 No. 6, from to MPORTANT WATER SANDS ande data on rate of water inflow and elevation to which water rose in hole. 3330 3350 feet.	to	l, from	577K			L SANDS OR ZO	NES Lo	806	7555
important water sands de data on rate of water inflow and elevation to which water rose in hole. 3330 3350 feet.	feet	, from	070	1	10	No. 4,	from	to	·
IMPORTANT WATER SANDS ide data on rate of water inflow and elevation to which water rose in hole. 3330 3350 1, from to No. 6, from No. 6	feet	1	77/Z	1	10	No. 5,	from	to	
ade data on rate of water inflow and elevation to which water rose in hole. 3330 3350 feet.	feet	3, from	TO/T		to	No. 6,	from	to	
tofeet	feet.	ł, from		······	to		· .	feet	
SIZE WEIGHT NEW OR AMOUNT SHOE CUT AND PERFORATIONS 5/8= 24# 366 Texas	AND PERFORATIONS PURPOSE	·	PER FO	OT USI	ED AMOUNT	SHOE	CUT AND PULLED FROM	PERFORATIONS	
	342.400	7/0"					rton	3952-3962	341140
# 144 4055 Hallimseton 1959-1902	1959-1969	**	<u> </u>	<i>T</i>	76//		Tr vv		
# 14# 4255 Halliburton 3952-3962 3972-3990 4074-4088	3952-3962 3972-3990 4074-4088							3972-3990 4074-4088	
3972-3990 4074-4088 4208-4222	3952~3962 3972~3990 4074~4088 4208~4222				NATION NO.	AND CEMENT	DIG PECOPD	3972-3990 4074-4088 4208-4222	
MUDDING AND CEMENTING RECORD ZE OF SIZE OF WHERE NO. SACKS METHOD MUD CRAVITY	MUD AMOUNT OF				NO. SACES	METHOD			
MUDDING AND CEMENTING RECORD MUDDING AND CEMENTING RECORD MUDDING AND CEMENT METHOD MUDGBAVITY MUDDING AND CEMENT USED GRAVITY	MUD AMOUNT OF		CASING	SET	NO. SACKS OF CEMENT	METHOD USED			
3972-3990 4074-4088 4208-4222	MUD AMOUNT OF	HOLE 6	5/8	366	NO. SACKS OF CEMENT 200	METHOD USED			
# 14# 4255 Halliburton 3952-3962	3952-3962						 	3000	
4255 Halliburton 3972-3962 3972-3990	3952~3962 3972~3990 4074~4088							3972-3990	
# 14# 4255 Halliburton 3972-3962 3972-3990 4074-4088 4208-4222	3952-3962 3972-3990 4074-4088 4208-4222							3972-3990 4074-4088 4208-4222	
3972-3990 4074-4088 4208-4222	3952~3962 3972~3990 4074~4088 4208~4222				MUDDING	AND CEMENT	ING RECORD	3972-3990 4074-4088 4208-4222	
MUDDING AND CEMENTING RECORD ZE OF SIZE OF WHERE NO. SACKS METHOD MUD ORAVITY	MUD AMOUNT OF				NO. SACES	METHOD			
MUDDING AND CEMENTING RECORD ZE OF SIZE OF WHERE NO. SACRS OF CEMENT USED GRAVITY MUDDING AND CEMENT USED GRAVITY	MUD AMOUNT OF		CASING	SET	NO. SACKS OF CEMENT	METHOD USED			
3972-3990 4074-4088 4208-4222	MUD AMOUNT OF	OLE 8	5/8	366	NO. SACKS OF CEMENT 200	METHOD USED			

CORD OF DRILL-STEM AND SPECIAL TF

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

n	1		0		4255	S USED				
Cable to	ools were : ols were u	used from sed from		feet 1 feet 1	io	feet,	and from	····	feet to	
						UCTION	and from.		Ieet to	
Put to P	Producina		•••••							
					0-	_				100
OIL WI			on during the first		urs was	••••••••••••			quid of which	
			37.2				% wate	r; and	%	was sediment. A
	,									
GAS WE	ELL: Th	e production	on during the first	24 ho	urs was	·	M,C.F. p	lus		barre
	liq	uid Hydroc	arbon. Shut in Pre	essurc.	lbs	•			s to si	
Length o	of Time S	hut in					et.			
PLE	CASE INI	DICATE B	ELOW FORMA	rion	TOPS (IN CON	FORMAN	CE WIT	H GEOGI	RAPHICAL SECT	ION OF STATE
			Southeastern 1	New 1	lexico				Northwestern	
			•••••••••••		Devonian				Ojo Alamo	
					Silurian				Kirtland-Fruitland	
			•			,			Pictured Cliffs	
T. 7 Ri	vers	***************************************		T.	McKee			т.	Menefee	
					Ellenburger				Point Lookout	
					Gr. Wash				Mancos	
					Granite					
					***************************************				Morrison	
					*				Penn	
T. Abo.		•••••••	••••••	T.						
		····		T.	**		······································			
T. Miss.	••••••	·		T.	FORMATIO	* * * * * * * * * * * * * * * * * * * *				
T. Miss.	1			Т.	FORMATIO	* * * * * * * * * * * * * * * * * * * *		т.		
T. Miss.	То	Thickness in Feet		T.	FORMATIO	* * * * * * * * * * * * * * * * * * * *			s	mation
From	т _о	Thickness in Feet		rmatic	FORMATIO	N RECO	ORD	T.	s	······································
From O 50	то 350 490	Thickness in Feet 350 140	gyp and p	rmatic	FORMATIO	N RECO	ORD	T.	s	······································
From	To 350 490 1460	Thickness in Feet 350 140 970	gyp and p	rmatic	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 +60 +90	To 350 490 1460 2490	Thickness in Feet 350 140 970 1030 840	gyp and produced bed a salt anhy.	rmatic	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 460 490 330	To 350 490 1460 2490 3330 3350	Thickness in Feet 350 140 970 1030 840 20	gyp and produced bed a salt anhy, red sand	rmatic	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 160 130 350	To 350 490 1460 2490 3330 3350 3800	Thickness in Feet 350 140 970 1030 840 20 450	gyp and g gyp red bed a salt anhy, red sand lime	red	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 460 490 350 350 952	To 350 490 1460 2490 3330 3350 3952 3962	Thickness in Feet 350 140 970 1030 840 20 450 152 10	gyp and red bed salt anhy, red sand lime sandy line	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 460 490 330 350 952 962	To 350 490 1460 2490 3330 3350 3952 3962 3972	Thickness in Feet 350 140 970 1030 840 20 450 152 10	gyp and red bed salt anhy, red sand line sandy line sandy line	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 160 190 330 350 350 252 272	To 350 490 1460 2490 3330 3350 3952 3962	Thickness in Feet 350 140 970 1030 840 20 450 152 10	gyp and red bed salt anhy, red sand lime sandy line	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 96 96 96 97 96 97 96 97 96	350 490 1460 2490 3330 3350 3952 3962 3972 3990 4074 4088	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84	gyp and red bed ralt anhy, red sand line sandy line sandy line sandy line sandy line sandy line sandy line	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 +60 +90 330 350 952 962 972 990 974	To 350 490 1460 2490 3330 3350 3952 3962 3962 3972 4074 4088 4208	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84 14	gyp and red bed salt anhy, red sand lime sandy lime sandy lime sandy lime sandy lime sandy lime	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 96 96 96 97 96 97 96 97 96	350 490 1460 2490 3330 3350 3952 3962 3972 3990 4074 4088	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84	gyp and red bed ralt anhy, red sand line sandy line sandy line sandy line sandy line sandy line sandy line	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 +60 +90 330 350 952 962 972 990 974	To 350 490 1460 2490 3330 3350 3952 3962 3962 3972 4074 4088 4208	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84 14	gyp and red bed salt anhy, red sand lime sandy lime sandy lime sandy lime sandy lime sandy lime	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 +60 +90 330 350 952 962 972 990 974	To 350 490 1460 2490 3330 3350 3952 3962 3962 3972 4074 4088 4208	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84 14	gyp and red bed salt anhy, red sand lime sandy lime sandy lime sandy lime sandy lime sandy lime	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 +60 +90 330 350 952 962 972 990 974	To 350 490 1460 2490 3330 3350 3952 3962 3962 3972 4074 4088 4208	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84 14	gyp and red bed salt anhy, red sand lime sandy lime sandy lime sandy lime sandy lime sandy lime	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 +60 +90 330 350 952 962 972 990 974	To 350 490 1460 2490 3330 3350 3952 3962 3962 3972 4074 4088 4208	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84 14	gyp and red bed salt anhy, red sand lime sandy lime sandy lime sandy lime sandy lime sandy lime	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 +60 +90 330 350 952 962 972 990 974	To 350 490 1460 2490 3330 3350 3952 3962 3962 3972 4074 4088 4208	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84 14	gyp and red bed salt anhy, red sand lime sandy lime sandy lime sandy lime sandy lime sandy lime	red and	FORMATIO	N RECO	ORD	T.	s	······································
From 0 50 90 +60 +90 330 350 952 962 972 990 974	To 350 490 1460 2490 3330 3350 3952 3962 3962 3972 4074 4088 4208	Thickness in Feet 350 140 970 1030 840 20 450 152 10 10 18 84 14	gyp and red bed salt anhy, red sand lime sandy lime sandy lime sandy lime sandy lime sandy lime	red and	FORMATIO	N RECO	ORD	T.	s	······································

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator. Boller & Michols	Address. Box 123, Maljamar, N.M.
Name & & McCulaff	Position or Title