| Form 9-331 (May 1963) | UNITED STATES BUBMIT IN TR DEPARTMEN OF THE INTERIOR (Other instruct Verse side) GEOLOGICAL SURVEY | IODS (F GLEASE DESIGNATION AND SEEIAL NO. NMO60196 |
|--|---|---|
| (Do not use this i | DRY NOTICES AND REPORTS ON WELLS form for proposals to drill or to deepen or plug back to a different reser Use "APPLICATION FOR PERMIT-" for such proposals.) | 6. IF INDIAN, ALLOTTEE OR TRIBE NAMI |
| 1. OIL GAB WELL WELL [2. NAME OF OPERATOR | X OTHER Water Injection Well | 7. UNIT AGREEMENT NAME Maljamar (Grayburg) 8. FARM OR LEASE NAME |
| Chevron 011 | Company | Maljamar Unit |
| 3. ADDRESS OF OPERATOR | • • • • • • • • • • • • • • • • • | 9. WELL NO. |
| | 60, Midland, Texas 79701 | 3 |
| See also space 17 belo | eport location clearly and in accordance with any State requirements.* | 10, FIELD AND POOL, OE WILDCAT Maljamar |
| At surface Unit A, 660' | FNL & FEL, Section 3, T-17-S, R-32-E | Grayburg-San Andres 11. SEC., T., R., M., OR BLE. AND SUBVEY OR AREA |
| 14. PERMIT NO. | U. S. GEOLOGIA | MMPM |
| 14. PERMIT NO. | 15. ELEVATIONS (Show whether Dr. RT. CR. STOR S NEW | 12. COUNTY OF PARISH 18. STATE |
| | GR 4272.5 | Lea New Mexic |
| 16. | Check Appropriate Box To Indicate Nature of Notice, R | eport, or Other Data |
| N | OTICE OF INTENTION TO: | SUBSEQUENT REPORT OF: |
| TEST WATES BRUT-OF | PULL OR ALTER CASING WATER SHUT-OF | P REPAIRING WELL |
| FRACTURE TREAT | MULTIPLE COMPLETE FRACTURE TREAT | |
| SHOOT OR ACIDIZE | ABANDON® SHOOTING OR AC | CIDIZING ABANDONMENT [®] X |
| REPAIR WELL (Other) | CHANGE PLANE (Other) | eport results of multiple completion on Well n or Recompletion Report and Log form.) |
| 3-22-75 Ran Spo cem tub 5 ¹ 2" 3-24-75 Ran Pul 3-25-75 Tag as 3-31-75 Cut mar | Led tubing and packer. Ran 5½" CIBP on with a tubing to 3985' and displaced hole with 9 otted 25 sacks cement. Pulled tubing to 330 eent. Pulled tubing to 2500' and spotted 25 oing to 1300' and spotted 25 sacks cement. ' casing at 390'. Pulled and laid down cast a tubing to 395' and could not get deeper. Led tubing to 295', reversed out cement with ged top of cement at 297'. Well turned over a water well. to off casing below ground level, welded stee ther. | .5 ppg mud laden fluid. 00', spotted 25 sacks 5 sacks cement. Pulled Pulled out tubing. Shot ing. Pumped 30 sacks cement. th fresh water. er to surface owner to use el plate. Set 4' steel |
| 18. I hereby certily that | the foregoing is true and correct J. W. Leonard TITLE Sr. Drilling En | gineer DATE May 9, 1975 |
| STONED 11 12- | PROFESSION NO DECHATA TITLE DI DI LITING DI | |
| (This space for Feder | al or State office use) | , parts, |
| | | DATE DATE |