

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other ☒ Water Injection Well

2. NAME OF OPERATOR
Chevron USA Inc.

3. ADDRESS OF OPERATOR
P.O. Box 1660 Midland TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) Unit L 990FWL 1980FSL Sec 4
AT SURFACE:
AT TOP PROD. INTERVAL: T-17S R-32-E
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☒
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
OCT 28 1980

U.S. GEOLOGICAL SURVEY
DOPES, NEW MEXICO

(Note: Report results of multiple completion or zone changes on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-22-80 Csg leak survey showed communication between tbg & tbg csg Annulus. NMOC requested well to be repaired in 7 days.

It is proposed to pull tbg & pkr. Clean out w/ bit & csg scraper to 4000'. Test csg. Acidize w/ 3000 gr 15% NACL Run new pkr & cement lined tbg.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Sam H. Givens TITLE Asst. Prod. Form. DATE 10-28-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

Oral Approval Geo. Stewart 10-28-80