

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 016799

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Maljamar (Grayburg)

8. FARM OR LEASE NAME

Maljamar Unit

9. WELL NO.

18

10. FIELD AREA OR WILDCAT

(Grayburg-San Andres)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

NMPM

Sec 4, T-17-S, R-32-E,

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER Water Injection Well

2. NAME OF OPERATOR

Chevron Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 1660, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Unit N, 1980' FNL, 660' FEL, Sec. 4, T-17-S, R-32-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 4218

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETION ☐ABANDON* ☒CHANGE PLANS ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*Work to commence third quarter 1975. Federal office will be notified to commencing
actual plugging operations.

1. Dig pit and cellar.

2. Run in hole with tubing, open ended, to 3900', displace hole with 9.5 ppg mud
laden fluid. Spot 25 sxs cement. Pull tubing to 2400' and spot 30 sxs cement.
Pull tubing to 1200' and spot 35 sxs cement. Pull out of hole with tubing.3. Perforate 5 1/2" casing at 373'. Establish circulation, pump sufficient cement
to circulate to surface via annulus leaving 5 1/2" casing full.4. Cut off casing 2-3' below ground level, set 4' marker. Back fill pits and cellar.
Clean up location as per federal or state requirements.

NOTICE TO ABANDON APPROVED FEB. 11, 1975 IS SUPERCEDED BY THIS APPROVAL.

18. I hereby certify that the foregoing is true and correct

SIGNED

E. T. Krysuik

TITLE Division Drilling Supt.

DATE July 30, 1975

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side