

Form 5-311
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE
(Other instructions on reverse side)

Form approved,
Budget Bureau No. 42-BU

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

LC-029406 (b)

6. IF DESIGN, ALLOTTEE OR TRUST NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

GRACE MITCHELL R

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

MALE C-SB

11. SEC., T., R., M., QUILN AND
SURVEY OR AREA

SEC. 6, T-17S, R-32E

12. COUNTY OR PARISH

LEA

N. MEX

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Continental Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 460, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL + 660' FWL, SEC 6

14. PERMIT NO.

15. FLUVATIONS (Show whether DE, EL, OR, etc.)

4080' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones per-
nent to this work.)

It is proposed to plug and abandon this well by
the following procedures.

Spot a 95 sack plug from TD to approx 3650'
(cover pipe from 3705' to 4136'). Fill well bore with
10# mud to within 130' of surface. Spot a 10 sack
cmt plug at surface and cap with dry hole marker.
Clear location for inspection.

AMENDMENT: In addition to above, place 100-lb cement plug
inside 4 1/2" casing at 2000-2100 feet and 800-900 feet.

18. I hereby certify that the foregoing is true and correct

SIGNED

M. E. Yeakley

TITLE Adm. Section Chief

DATE 6-25-70

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED
AS AMENDED
AUG 10 1970

DATE

USGS-5

FILE

*See Instructions on Reverse Side

REMOVED

JUN 11 1970

RECEIVED
JUN 11 1970